# **ABSOLUTE Coolant Proof Caliper**

SERIES 500 — with Dust/Water Protection Conforming to IP67 Level

# **FEATURES**

- Can be used in workshop conditions exposed to coolant, water, dust or oil.
- Easy to use no need to wipe or clean the
- Advanced design styling.


- Incorporates absolute measurement
- Automatic power-on/off.
- Data output function.
- With thumb roller.
- Supplied in fitted plastic case.











Built-in ABS (absolute) scale means that these calipers are ready to use immediately after power-on without origin resetting. It's as easy as vernier caliper measurements.



# Certificate of inspection

Project term Consensus	Element Department & coules Element	Department - Department - Laborate and laborate			1	
Mark to Marks	(3.789)	Plante in heavy	Sincerones 1	Energy Subsects	percentage at	
into to i Reference	49.40	- 64	437	-	444	
MONTHS AND	041911 0.00ms 0.0ms	4 10 10 10 10 10	****	100 100 101 401	10 10 10	Challenger Challenger
ternere (emperature) (emperature de finitionise)	m H					
Of the specific course (seek Consts. )		40.9	-8-00W 6-00W	-	-	
			4100	-	.77.	
						1000
					-	Asset bring.
				-		\$458.00

#### **Technical Data**

Refer to the list of specifications .0005 "/0.01mm or 0.01mm Accuracy: Resolution: Repeatability: .0005" / 0.01mm Display: LCD

Length standard: ABSOLUTE electromagnetic induction

linear encoder Max. response speed: Unlimited Battery: SR44 (1 pc./2 pcs\*), 938882
Battery life: Approx. 3 years under normal use (1 year: over 12" / 300mm models)

Dust/Water protection level: IP67 \*0 - 300mm model

## **Function**

Origin-set, Zero-setting, Automatic power on/off, Data output, inch/mm conversion (on inch/metric models only) Low voltage, Counting value composition error

## **Optional Accessories**

**05CZA624**: SPC cable with data switch (40" / 1m) **05CZA625**: SPC cable with data switch (80" / 2m)





Measurement data output function is available with a water-resistant SPC cable.