



Stage plate black



Stage plate white

EDUCATIONAL LINE

The robust and practical model for school, training establishment, workshops and laboratory

Features

- The KERN OSF 438 and OSF 439 is a very practical and easy to use stereo microscope.
- This microscope can be safely and easily moved around thanks to its built-in handle.
- Its mechanical stand makes it particularly stable.
- In addition to the very good optical properties, its ergonomically designed working surface offers the best possible ease of use in this class.
- This model is optimally suited to schools,


- workshops and training establishments.
- A strong LED incident and transmitted illumination unit reliably delivers the necessary light.
- The multitude of objective combinations and eyepieces are all you can wish for.
- The eyepieces are fixed in the tube to protect them against loss or damage.

Technical data

- Optical system: Greenough
- Brightness adjustable
- Tube: 45° inclined
- Interpupillary distance: 55 – 75 mm
- Diopter adjustment (one-sided)
- Packing dimensions WxDxH 290x225x340 mm
- Net weight approx. 2,5 kg

Please find detailed information in the following charts.

STANDARD



Model	Standard configuration						
	Tube	Eyepiece	Field of view mm	Objective	Stand	Illumination	
KERN OSF 438	Binocular	WF 10x Ø 20 mm	Ø 20	1x / 2x / 3x	Arm curved	1W LED (incident); 0,35W LED (transmitting)	
OSF 439	Binocular	WF 10x Ø 20 mm	Ø 20	1x / 2x / 4x	Arm curved	1W LED (incident); 0,35W LED (transmitting)	

Eyepiece	Specifications - Objectives				
	Magnification	1x	2x	3x	4x
WF 5x	Total magnification	5x	10x	15x	20x
	Field of view mm	Ø 20	Ø 10	Ø 6,7	Ø 5
WF 10x	Total magnification	10x	20x	30x	40x
	Field of view mm	Ø 20	Ø 10	Ø 6,7	Ø 5
WF 15x	Total magnification	15x	30x	45x	60x
	Field of view mm	Ø 15	Ø 7,5	Ø 5	Ø 3,7
WF 20x	Total magnification	20x	40x	60x	80x
	Field of view mm	Ø 10	Ø 6,5	Ø 4,3	Ø 3,2
Working distance		57 mm	57 mm	57 mm	57 mm

Model outfit		Model KERN		Order number	
		OSF 438	OSF 439		
Eyepieces	WF 5x / Ø 16,2 mm	○○	○○	OZB-A4101	
	WF 10x / Ø 20 mm	●●	●●	OZB-A4102	
	WF 15x / Ø 15 mm	○○	○○	OZB-A4103	
	WF 20x / Ø 10 mm	○○	○○	OZB-A4104	
Stands	Arm curved, incl. handle, with LED illumination (0,35W transmitting + 1W incident)	●	●		
Stage plate	Frosted glass / Ø 59,5 mm	●	●	OZB-A4815	
	Black-white / Ø 59,5 mm	●	●	OZB-A4816	
External illumination	Please find the information about external illumination units in the catalogue from page 68 and on our website www.kern-sohn.com				

● = Standard configuration

○ = Option