

# XT500 Large Diameter 3-point Bore Gauge

## At a Glance



Range: 300-500mm



Non Bluetooth is available upon request



The **Bowers XT500 large diameter 3-point bore-gauge** has been designed specifically for the measurement of internal diameters between 300 and 500mm. The newly designed constant-force digital readout ensures that the measuring pressure remains constant throughout the measurement whilst radiussed measuring anvils provide optimum centralisation in the part. Anvil sets are supplied in 25mm steps (300-325, 325-350 etc) and each set has been manufactured to the exact toleranced size. The 300-325mm anvils are the master reference set and are used for setting the gauge in the setting ring. The other anvil sets are then fitted as required without further re-setting. This means that only one 300mm setting ring is required to set the gauge for all diameters in the full 300-500mm range of the instrument.

## Features

- New constant-force digital readout
- Single 300mm setting ring covers full range
- Radiussed anvils of tool-steel for optimum centering
- Accuracy: 15µm
- Repeatability: 3µm
- IP67 electronics
- Proximity output with built-in Bluetooth
- Resolution 0.01/0.001mm. Metric/inch switchable
- Fast accurate measurement
- Extensions available for deeper bores
- UKAS certificate with setting ring
- Certificate of conformity with bore gauge
- Supplied in a fitted case

31

## Visit our Website

For more information please go to our website using the QR code.



BOWERS GROUP

# XT500 Large Diameter 3-point Bore Gauge

**Individual instruments:** Supplied with digital display unit, measuring head with exchangeable anvils and setting ring with UKAS certificate

Code No	Range (mm)	Accuracy (µm)	Depth (mm)	Setting Ring (mm)
XT5001M-BT	300-325	15	120	300
XT5002M-BT	300-325, 325-350	15	120	300
XT5003M-BT	300-325, 350-375	15	120	300
XT5004M-BT	300-325, 375-400	15	120	300
XT5005M-BT	300-325, 400-425	15	120	300
XT5006M-BT	300-325, 425-450	15	120	300
XT5007M-BT	300-325, 450-475	15	120	300
XT5008M-BT	300-325, 475-500	15	120	300

**Data Transmission**

Code No	Description
30-926-6721	Sylvac Proximity USB Cable
25-604-064	Wireless Proximity Module Transmitter
25-604-001	USB Receiver

**Sets:** Supplied with digital display unit, measuring head with exchangeable anvils and setting ring with UKAS certificate

Code No	Range (mm)
SXT3000M-BT	300-400
SXT4000M-BT	300-325, 400-500
SXT5000M-BT	300-500

**Extensions to the XT500**

Code No	Range (mm)
DHEXT500	500
DHEXT1000	1000



The Bowers XT500 with extension for deeper bores. We can also offer the XT500 with extensions and an increased force XTH pistol grip. Please contact Bowers for price and availability.