

Crane scale KERN HCD



High-resolution crane scale for loads up to 300 kg

**Features**

- Fully-equipped crane scale for low to medium load ranges. The solid design guarantees that extra level of safety (TÜV tested). Thanks to the large LCD display and the remote control which is delivered as standard, it can also be operated safely from a distance and results can be read off
- **1** With the TÜV certification mark, the scale meets the requirements of the standard EN 13155 (Non-fixed load lifting attachments/ Breakage resistance) and EN 61010-1 (Electrical safety)
- High level of mobility: thanks to battery pack operation, compact construction and low weight, it is suitable for use in several locations (production, warehouse, dispatch department, etc.)
- Hold function: For easy reading of the weighing result, the display can be “frozen” in different ways. Either automatically when the weighing value remains unchanged or manually by pressing the Hold key

- Tare: Resets the display to “0” when there is a load on the scale. Now removed or added loads are directly displayed
- Battery level indicator, LED visual display
- Large high-contrast display that is easy to read
- Standby function: display automatically switched off after 5 min without a change of load. Automatic activation with the touch of a key
- Hook with safety catch, revolving
- Shackle and safety catch made of nickel-plated steel
- **2** Infrared remote control standard. Range up to 20 m. All functions can be selected. W×D×H 65×24×100 mm. Batteries included

**Technical data**

- Backlit LCD display digit height 28 mm
- Ready for use: Batteries included, 4×1.5 V AA, operating time up to 100 h
- Precision: 0,2 % of [Max]
- Permissible ambient temperature 5 °C/40 °C

**Accessories**

- Internal rechargeable battery pack for Load lifting attachments, operating time up to 50 h without backlight, charging time approx. 12 h, KERN HCD-A01

STANDARD

CAL EXT
 UNIT
 BATT
 DMS
 1 DAY

OPTION

ACCU
 DAkKS +3 DAYS

Model	Weighing capacity [Max] kg	Readability [d] g	Net weight approx. kg	3 Dimensions							Option	
				A mm	B mm	C mm	D mm	E mm	F mm	G mm	DAkKS Calibr. Certificate	DAkKS KERN
<b>KERN</b>												
HCD 60K-2	60	20	1,10	150	79	97	276	250	26	18		963-129H
HCD 100K-2	150	50	1,10	150	79	97	276	250	26	18		963-129H
HCD 300K-1	300	100	1,10	150	79	97	276	250	26	18		963-129H
Dual-range balance switches automatically to the next largest weighing capacity [Max] and readability [d]												
HCD 100K-2D	60   150	20   50	1,10	150	79	97	276	250	26	18		963-129H
HCD 300K-2D	150   300	50   100	1,10	150	79	97	276	250	26	18		963-129H